

- [54] SEALANT FILLER FOR SMALL VOLUMES  
CONTAINING AN ACRYLIC LATEX, SAND,  
BENTONITE, PORTLAND CEMENT AND A  
POLYHYDRIC ALCOHOL

[76] Inventor: **Mario J. Basile**, 8512 Fifth Ave.,  
Brooklyn, N.Y. 11209

[22] Filed: **Jan. 9, 1974**

[21] Appl. No.: **431,842**

[52] U.S. Cl. .... **264/35**; 106/111; 260/29.6 R;  
260/29.6 S; 260/42.13; 260/33.4 PQ; 264/36

[51] Int. Cl.<sup>2</sup> ..... **E04B 1/16**

[58] Field of Search ..... 260/29.6 S, 29.6 R, 42.13,  
260/33.4 PQ; 106/111; 264/35, 36

[56] **References Cited**

**UNITED STATES PATENTS**

2,580,230	12/1951	Kunze et al. ....	260/29.6
2,884,396	4/1959	Allegretti .....	260/29.6

3,196,122	7/1955	Evans .....	260/29.6
3,256,223	6/1966	Heijmer .....	260/29.6
3,493,529	2/1970	Krottinger et al. ....	260/29.6
3,522,068	7/1970	Bastian et al. ....	260/29.6
3,547,853	12/1970	Kalandiak .....	260/29.6
3,706,696	12/1972	Bernett et al. ....	260/29.6

*Primary Examiner*—Eugene C. Rzucidlo

*Attorney, Agent, or Firm*—Howard C. Miskin

[57]

**ABSTRACT**

A two package sealant filler includes as a first paste component a dispersion of sand in a water based acrylic latex and as a second highly viscous component, a dispersion of bentonite and Portland cement in glycerine. In use, the first component and a minor amount of the second component are intimately admixed and applied to the work area where it cures throughout into an integral elastomeric mass having the appearance of concrete.

**5 Claims, No Drawings**